

G2700 SERIES

	SPECIFICATIONS			
MODEL	G2700 HD	G2700 X-Tra HD	G2700 HD+	G2700 X-Tra HD+
ENGINE	50 hp	50 hp	50 hp	50 hp
SERVICE WEIGHT	5,622 lbs	5,622 lbs	5,732 lbs	5,732 lbs
LIFTING HEIGHT	116.7 in.	98.3 in.	116.7 in.	98.3 in.
TIPPING LOAD	5,236 lbs	6,283 lbs	5,291 lbs	6,393 lbs
WORKING HYDRAULICS	13.5/18.5 (opt.)GPM	13.5/18.5 (opt.)GPM	13.5/18.5/21 (opt.)GPM	13.5/18.5/21 (opt.)GPM
MAX. SPEED	6.2/15.5 mph	6.2/15.5 mph	6.2/18.6 mph	6.2./18.6 mph



Less tire wear and ground damage



Enhanced operator comfort through articulation and oscillation



Bridging the gap between skid steer loaders and larger wheel loades Safe and ergonomic operator station with

side entry



Higher lift heights and higher tipping loads compared to service weight



The GiANT G2700HD compact articulating wheel loader is powered by a Kubota 50 HP, 3-cylinder, turbo diesel engine. A diesel oxidation catalyst (DOC) and diesel particulate filter (DPF) aid the engine to achieve Stage V emission compliance, the cleanest in the industry! This machine is available in two boom configurations, X-Tra and Z-Bar, both utilizing the standard skid steer quick attach plate (SSQA). The G2700 also comes standard with a 2-speed gearbox, limited slip differentials and electric locking differentials for the HD PLUS model. Planetary final drives deliver torque to the ground and achieve impressive top speeds of 15.5mph - 18mph (depending on model). This machine is available open station, deluxe ROPS or with full cab and heat, all offering a safe and ergonomic work environment. In addition, the G2700 frame is equipped with an oscillation joint, helping to improve ride quality and limit ground pressure. A few of the available options include tire profiles for various terrains, road lights for safe travel, 21gpm hydraulic flow, pro-inching and boom suspension. The G2700 has the power and efficiency to comfortably operate in the agriculture, construction, landscaping and snow removal industries.

GiANT Loaders North America reserves the right to make changes in specification at any time without notice or obligation.









DIMENSIONS

		G2700		G2700
	G2700 HD	X-Tra HD	G2700 HD+	X-Tra HD+
Α	64.9 in.	66.9 in.	64.9 in.	66.9 in.
В	134.1 in.	136.5 in.	134.1 in.	136.5 in.
С	164.4 in.	166.9 in.	164.4 in.	166.9 in.
G	54.3 in.	54.3 in.	54.3 in.	54.3 in.
н	92.1 in.	92.1 in.	92.1 in.	92.1 in.
I	92.1 in.	92.1 in.	92.1 in.	92.1 in.
J	66.9 in.	59.6 in.	66.9 in.	59.6 in.
К	87.0 in.	69.0 in.	87.0 in.	69.0 in.
L	117.5 in.	99.1 in.	117.5 in.	99.1 in.
М	140.6 in.	122.2 in.	140.6 in.	122.2 in.
Ν	45°	42°	45°	42°
0	52.7°	46.4°	52.7°	46.4°
Р	37.4°	36.5°	37.4°	36.5°
Q	25.3°	25.3°	25.3°	25.3°
R	Ø 33.5 in.	Ø 33.5 in.	Ø 33.5 in.	Ø 33.5 in.
1 A	117 in.	119.9 in.	117 in.	119.9 in.
1B	100.8 in.	103.3 in.	100.8 in.	103.3 in.
1C	57.5 in.	60 in.	57.5 in.	60 in.
1D	43.3 in.	43.3 in.	43.3 in.	43.3 in.





🖻 f in 🞯



TIPPING LOADS

	G2700 HD	G2700 X-Tra HD	G2700 HD+	G2700 X-Tra HD+
S	5,236 lbs	6,283 lbs	5,291 lbs	6,393 lbs
Т	3,968 lbs	4,630 lbs	4,012 lbs	4,850 lbs
U	2,976 lbs	3,461 lbs	3,086 lbs	3,527 lbs
V	2,370 lbs	2,646 lbs	2,425 lbs	2,700 lbs
W	6,173 lbs	6,504 lbs	6,283 lbs	6,614 lbs
Χ	3,968 lbs	4,300 lbs	4,189 lbs	4,409 lbs
Υ	3,086 lbs	3,307 lbs	3,197 lbs	3,483 lbs

GiANT Loaders North America reserves the right to make changes in specification at any time without notice or obligation.

giantloaders.com